



United Security Products, Inc.

Cellular Auto Voice Dialer Security Systems

Onsite or at Remote Locations, USP's Cellular Auto Voice Dialer Security Systems offer Reliable Low Cost Monitoring Solutions. No phone line, No contract, and No monitoring fees required. Secures RVs, Cabins, Boats, Storage Garages, Containers, Shops, Manufacturing Plants, etc. Monitors Signal Change in Operating Status of Remote Equipment or Machinery. Backs Up primary alarm system if phone lines are cut

About USP

United Security Products, Inc. has supplied quality products to the security alarm industry for over 40 years, with proven performance in more than 100 million installations. Security systems dealers rely on USP for the most innovative products in the security industry. For your next installation, be sure to specify USP products.

CVD-2000

Full Featured Security System with 4 Independent Voice Channels and Universal Cellular Dialer Backup with Cell Phone/SIM Card



CVD-2000 is a completely self-contained, four-channel monitoring system and cellular automatic voice dialer. Trigger events are announced via recorded voice message delivered by the cell phone when the call is answered.

Representing an exciting new level of achievement, the CVD-2000 combines technologically advanced features, ease of programming and reliable operation in a compact, unobtrusive dialer completely compatible with any security alarm system.

Models

- CVD-2000 - your cell phone and service
- CVD-2000P - comes with Cell Phone
- CVD-2000PS - comes with Cell Phone and 1 year/400 minutes prepaid Cellular Service Included

Features

- AT&T / Verizon Compatible - Operates with Most Cellular Providers Worldwide – Bluetooth Capability
- Model PS Includes \$100 one year prepaid Cellular Service – No Contracts and No Monthly Fee
- 4 Separate Voice Dialer Channels/Zones
- Built-in Line Seizure
- Automatically Calls Up to 8 telephones, cell phones, etc.
- Can be used with landline – Instantly switches to cellular calling if landline is cut
- Metal Cabinet with Cam Lock included
- EEPROM Memory retains programming if power is lost

Specifications

Power source: 9-18VDC

Current (OPERATE mode - standby): 28mA typical.

Current (OPERATE mode - dialing): 100mA max.

Activation:

- 1) N.C. Activation: dialer activates when an "open" is detected
- 2) N.O. Activation: dialer activates when a "close" is detected
- 3) Voltage Activation:
 - N.C. (applied voltage: Min. +5VDC, Max. +28VDC)
 - N.O. (loss of continuous voltage: Min. 0VDC, Max. 0.25VDC)

Max. Digits for outgoing numbers: 50

Operating temperature range: -18 to 55 C (0 to 130 F)

Dimensions (inches): 13.5x11.5x6.5in

Weight (ounces): 11 Lbs

Mounting: Wall or Flat Surface

Case Material: Steel

Color: Beige

Warranty: 1 Year

